



Kontrol 800 Tech

The Kontrol 800 Tech is a dedicated multi-parameter controller for complex applications that require a number of chemical parameters to be checked at the same time.

The unit features independent proportional control output measures, four programmable frequency Outputs, RS485 serial port with ModBus protocol, Four Powered Output Relays and two Relays dry contact, a map configuration function to assign relays, frequency and mA outputs.

Probe quality checking and data logging capability are also available.

TECHNICAL CHARACTERISTICS

- Power Supply: 100-240 Vac 50/60 Hz, 15 Watt (Class 1)
- System duration: 24 hours a day, 7 days a week for 5 years
- Operating temperature: 0 to 40°C, relative humidity 0 to 95% (without condensation)
- Data display: Graphic Display 240X128 Pixel / White backlight
- Keyboard: membrane 7 Keys
- Cable connections: Dual row connectors
- Six Relays: Four 100 to 240Vac Powered relays and Two dry contact relays
- Output Modules associated with the chemical measurements
- Four 4-20 mA Current Output channel, 500 Ohm maximum load
- Four Frequency Output channel (Open Collector NPN/PNP) 1 - 120 pulses/min
- Flow(pull up) (Input for Reed sensor)
- Hold function by voltage input (15-30 Vdc) and Reed input
- Internal Power Supply for Sensor (24 Vdc @30mA)
- RS485 Serial Port (ModBus Standard Protocol)
- Temperature Probe input
- Modules integrated technology with Chlorine measure for water treatment application
- Full Mode function allows to set the free-viewing configuration to the end user (*only FM model*)
- Preset function to assign a viewing configuration to the specific application (*only FM model*)
- Clock module with backup battery
- Enclosure Box in Wall mounting, ABS material, IP65 Full Box (L:278 x H: 285 x D:139.5)

KEY CODE

K	Kontrol									
	800	Kontrol 800								
		G	GRAPHIC DISPLAY							
			00	Basic Model						
			01	Basic Model + Amperometric Chlorine						
			02	Basic Model + pH + Redox						
			03	Basic Model + pH + Amperometric Chlorine						
			04	Basic Model + pH + Redox + Amperometric Chlorine						
			07	Basic Model + pH + Potentiostatic Chlorine						
			08	Basic Model + pH + Redox + Potentiostatic Chlorine						
			12	Basic Model + pH + Redox + Amperometric Chlorine + Turbidity						
			13	Basic Model + pH + Redox + Potentiostatic Chlorine 1 + Potentiostatic Chlorine 2						
			14	Basic Model + pH + Redox + Amperometric Chlorine + Potentiostatic Chlorine 1 + Turbidity						
			FM (Full Mode)	Basic Model + pH + Redox + Amperometric Chlorine + Potentiostatic Chlorine 1 + Turbidity + EC-Conductivity						
				W	Wall type rated IP65					
					M	Switching 80÷265 Vac				
						0	FREE/CUSTOM			
							0	FREE/CUSTOM		
								0	FREE/CUSTOM	
K	800	G	FM	W	M	0	0	0		

PRODUCT LINE

	pH	Redox	EC- Conductivity	Amperometric Chlorine	Potentiostatic Chlorine	Turbidity	Temperature
K800G01WM000				•			•
K800G02WM000	•	•					•
K800G03WM000	•			•			•
K800G04WM000	•	•		•			•
K800G07WM000	•				•		•
K800G08WM000	•	•			•		•
K800G12WM000	•	•		•		•	•
K800G13WM000	•	•			•	•	•
K800G14WM000	•	•		•	•	•	•
K800GFMWM000	•	•	•	•	•	•	•

MEASURE RANGE

pH	0 - 14 pH	± 0.01 pH
Redox	± 1.500 mV	± 1 mV
Conductivity	0.054 – 200.000 µS	± 2 %
Dissolved Oxygen	0 - 20 ppm	± 2 %
Flow Rate	0 - 99.999 l/sec.	± 0.5 Hz
Chlorine	0 - 200 ppm	± 0.01 ppm
PAA	0 - 99.000 ppm	± 0.01 ppm
H2O2	0 - 99.000 ppm	± 0.01 ppm
Bromine	0 - 200 ppm	± 0.01 ppm
Ozone	0 - 99.000 ppm	± 0.01 ppm
Turbidity	0 - 4.000 NTU	± 2 %
Temperature	0 - 100 °C (-32 - 212 °F ± 1.8°F)	± 0.2 °C

DIMENSIONS

