

Water Treatment

ELITE.PRC

DOSING SYSTEM



Main characteristics

- Digital system for CL, pH, Rx control with 2 peristaltic pumps for chemical regulation for indoor and outdoor swimming pools.
- Free Chlorine measurement with amperometric probe (copper platinum electrode)
- 16 characters x 2 lines Display (Blue / White)
- Power supply: 230Vac 50/60 Hz
- Panel mounted model available

Water Treatment



Technical features

CONSUMPTION	WEIGHT	DIMENSIONS	RANGE	FLOW RATE	PRESSURE	POWER SUPPLY
18 w	1 Kg	286 x 234 x 108 mm	0 ÷ 14Ph 0 ÷ 1000 mV 0-5 PPM Cl	1,5 or 5 L/h	1,5 bar	230 Vac

ELITE.PRC

POOL DIMENSIONS	1,5 L/h – Indoor: from 1 up to 150 m ³ ; Outdoor: from 1 up to 110 m ³ 5 L/h – Indoor: from 50 m ³ to 350 m ³ ; Outdoor: from 50 m ³ to 300 m ³
2 PERISTALTIC DOSING PUMPS	Santoprene tube Flow rate: 1,5 or 5 L/h ; Pressure 1,5 bar
MAIN BOARD	Alphanumeric display (16 characters x 2 lines) Power supply: 230Vac 50/60Hz
ENCLOSURE BOX	Dimensions: 286 x 234 x 108 mm ; PP Box ; Protection degree: IP65

Installation Kit



Example of Installation

